AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (currently amended) Building A building composed of comprising:

a sill (20);

outside external wall components (10) standing on the sill (20), the wall components being double-walled and comprised of panels (11) joined to one another and spaced at a distance from one another via spacer elements (12), the panels defining a cavity (13) within the wall components (10) and extending from the sill (20);

roof components (50) connected to the wall components (10), and optionally ceiling components (40), at least the outside wall components (10) being made double walled, and having panels (11) which are connected to one another with the formation of at least one cavity (13) in the outside wall component (10) via spacers (12) with a distance from one another, in the cavity (13) between the panels (11) of the outside wall components (10), characterized in that the means (30) for supplying heat is located solely in the lower area of the outside wall components (10) (Figures 1, 3, 4, to 7)

a heat source (30) for supplying heat into the cavity (13) within the wall components (10), the heat source (30) provided entirely within the sill (20) on which the external wall components (10) stand.

- 2. (currently amended) Building The building as claimed in claim 1, wherein there is means (30) for supplying heat in a sill (20) on which the outside wall components (10) stand vertically (Figure 2).
- 3. (currently amended) $\frac{\text{Building}}{\text{Building}}$ The building as claimed in claim 2,

wherein the sill (20) is U-shaped in cross section, and wherein the panels (11) of the outside wall components (10) stand vertically on the legs (22) of the sill (20), and wherein which the legs (22) of the sill (20) point up (Figure 2).

- 4. (currently amended) Building The building as claimed in claim 1, wherein the heating means (30) has a rod-shaped heat source (31) (Figure 2) is rod-shaped.
- 5. (currently amended) $\frac{\text{Building}}{\text{Building}}$ The building as claimed in claim 4, wherein the rod-shaped heat source $\frac{\text{(31)}}{\text{is}}$

 $\underline{\text{one of}}$ an electrical resistance heating rod $\underline{\text{or}}$ $\underline{\text{and a}}$ heating wire.

6. (currently amended) Building The building as claimed in claim 4,

wherein the rod-shaped heat source $\frac{(31)}{}$ is a pipe $(32)_{\underline{\i}}$ and

7. (currently amended) Building The building as claimed in claim 4 wherein the rod-shaped heat source (31) is inserted into essentially U-shaped supports (33), and

wherein which the U-shaped supports (33) are inserted into the cavity of the sill (20) which is open to the top (Figure 2).

8. (currently amended) Building The building as claimed in claim 7, wherein there is further comprising:

an insulating layer (34) between the supports (33) and the crosspiece (21) of the sill (20) (Figure 2).

9. (currently amended) $\frac{\text{Building}}{\text{Building}}$ The building as claimed in claim 7,

wherein the end surfaces (35)) of the <u>U-shaped</u> supports (33) which are provided next to the holding space (36) open to the top for the rod-shaped heat source (31), and

wherein end surfaces (35) of the U-shaped supports (33) are aligned sloping toward the legs (22) of the sill (20) (Figure 2).

10. (currently amended) $\frac{\text{Building}}{\text{Building}}$ The building as claimed in claim 1, $\frac{\text{further comprising:}}{\text{claimed in claim 1}}$

ceiling components (40) having wherein in the an area of the ceiling components (40) which adjoin adjoining the out side external wall components (10),

the area provided with there are openings (41) (Figures 4, 5).

11. (currently amended) Building The building as claimed in claim 10,

wherein the ceiling components (40) are comprised of ceiling panels, and

wherein there are the openings (41) are in the ceiling panels of the ceiling component components (40).

12. (currently amended) Building The building as claim in claim 11, wherein the side ends of the ceiling component components (40) are closed. by panels (42) (Figures 4, 5)

13. (currently amended) Building The building as claimed in claim 1,

wherein in the position of use of the roof components (50) are comprised of lower panels, of the roof components (50) there are the lower panels having recesses (52) (Figures 6, 7).

- 14. (currently amended) Building The building as claimed in claim 13, wherein the side ends of the roof elements components (50) are closed by panels (53) (Figures 6, 7).
- 15. (currently amended) Building The building as claimed in claim 12, wherein the sealing panels (42) and (53) (42, 53) are flush with the outer panels (11) of the wall components (10) (Figures 4 to 7).
- 16. (currently amended) Building The building as claimed in claim 1, wherein the pipes (32) of the heating means heat source (30) is comprised of pipes (32), the pipes (32) being are attached in the area of the sill (20) by supports (61),

the supports (61) anchored to with a beam (60) which runs running lengthwise and which is located in the lower area of the cavity (13) of the wall components (10) (Figure 14).

- 17. (currently amended) Building The building as claimed in claim 16, wherein the support (60) is held in a profile strip (62) (Figure 14).
- 18. (currently amended) Building The building as claimed in claim 17,

wherein the profile strip (62) has a horizontal crosspiece (63), on which and

 $\frac{\text{wherein the lower ends of the panels (11) of the wall}}{\text{component (10)}} \text{ stand vertically } \underline{\text{on the horizontal crosspiece}}$ (63).

19. (currently amended) Building The building as claimed in claim 17,

wherein the profile strip (62) has legs (64) which $\frac{1}{2}$ project projecting from the horizontal crosspiece (63) of the $\frac{1}{2}$ profile strip (62), and

wherein between which the beam (60) which runs lengthwise is located between the legs (64) of the profile strip (62) (Figure 14).

20. (currently amended) Building The building as claimed in claim 19, wherein the legs (64) of the profile strip

(62) adjoin the lengthwise running side surfaces of the beam (60)

which runs lengthwise via projection projections (65) (Figure 14).

- 21. (currently amended) Building The building as claimed in claim 20, wherein the projections (65) are lengthwise running ribs which run lengthwise.
- 22. (currently amended) Building The building as claimed in claim 21, wherein the projections (65) are knob-like projections.